

IMPACT RESISTANT TIES



IMPACT RESISTANT TIES

Impact-Resistant, Heat-Stabilized Nylon prevents cable ties from cracking and breaking due to repeated high impacts, vibration, extreme temperatures, or weathering.

- Increased flexibility and toughness
- Resists high impact fatigue and endures vibrations
- Resists cold temperature fracturing down to -40°F
- Provides high operating temperatures of 230°F
- Allows cable tie installation at -4°F
- Weather resistant UV Black for outdoor use and sun protection

ACT Part Number	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tensile Strength	Bundle Dia. Inch/mm	Per Bag	Per Case
AL-05-40-IT-30-C	5.84/148.33	.14/3.55	.04/1.24	40 lb.	1.43/36.42	100	10,000
AL-05-40-IT-30-M						1,000	
AL-07-50-IT-30-C	7.56/192.07	.18/4.57	.05/1.32	50 lb.	1.87/47.62	100	10,000
AL-07-50-IT-30-M						1,000	
AL-11-50-IT-30-C	11.25/285.75	.18/4.57	.05/1.32	50 lb.	3.06/77.77	100	5,000
AL-11-50-IT-30-D						500	
AL-14-50-IT-30-C	14.25/361.95	.18/4.57	.05/1.32	50 lb.	4.00/101.60	100	5,000
AL-14-50-IT-30-D						500	
AL-08-120-IT-30-C	8.70/220.98	.30/7.62	.07/1.93	120 lb.	2.06/52.30	100	3,000
AL-14-120-IT-30-C	15.09/383.36	.30/7.62	.07/1.93	120 lb.	4.06/103.18	100	2,000

Mounting Hole Impact Ties

AL-07-50-MH-IT-30-C	8.00/203.20	.17/4.49	.05/1.32	50 lb.	1.75/44.45	100	5,000
AL-14-120-MH-IT-30-C	15.75/400.05	.29/7.56	.07/1.93	120 lb.	4.06/103.17	100	2,000

MH Cable Tie: 7" = #10 screw, 14" = .25" screw.

Sold in case quantities

Related product lines



Heat Stabilized
UV Black
Nylon 6/6



Cold Weather



Nylon 12

ACT
ADVANCED CABLE TIES, INC.
245 Suffolk Lane, Gardner, MA 01440
Phone: 800.861.7228 - Fax: 978.630.3999
sales@actfs.com

